

ENQUIRY -/ ORDER FORM FOR LIGHT FITTINGS

To: MAX MÜLLER AG Process Illumination and Visual Observation Systems Hagmattstrasse 19, CH - 4123 Allschwil E-mail: blt@maxmuellerag.com Telephone: +41 61 487 92 92 Telefax: +41 61 487 92 99	From: Company: Street: Postcode: Town: Telephone: Telefax: Person to contact :
--	---

1. Introduction

This enquiry / order form has been created in order to help your design engineers as well as the engineers of MAX MÜLLER AG to define the most adapted solution for light fittings.

Please fill it in as precisely as possible. Thank you.

Order
 Enquiry

2. General information and operating conditions

Size of vessel / equipment: Diameter x Height m
 Vertical
 Horizontal
 Max. temperature of the product in the vessel: ° Celsius
 Quality of product in the vessel:

3. Light fittings

Requested type of MAX MÜLLER catalogue	to fit sightglass type / DN / PN	No. of pieces
1.
2.

Characteristics:

1. - Power supply: V AC DC
 - Power: W
 - Operation:

- Permanent operation
- Semi-permanent operation (with built-in or external ON / OFF switch)
- Momentaneous operation (with built-in or external momentaneous push button)
- Timed (with built-in or external timer)

 Remark: Built-in ON / OFF switch only possible on safe area light fittings

- Light fitting for:

- Hazardous area (Ex) Ex- Classification: Ex d IIC T.....
 Ex de IIC T.....
- Safe area

-Special request(s)/options:

- Flood reflector (large beam) "F1"
- Timer "V" T= min
- External timer "U3"
- Momentaneous push button "D"
- Vertical cable gland "K1" (series FHEL / FHEL LED)
- Horizontal cable gland "K2" (series EdelEx / fibroLUX E / (B)KVLR (LED) / KLR)
- Transport handle "T"
- Stainless steel outside screws
- Spotlight adapter "SA" (series fibroLUX®)
- Length of the lightpipe (series fibroLUX®)
 - 0,5 m 1 m 2 m 3 m 4 m 5 m
- Acryl Painting "K"
- Timer "U" T= min
- External timer "RU3"
- ON / OFF switch "E"

